

Hedge cutter & hedge trimmer



Facts and technical data on hedge cutter and hedge trimmer for the City Ranger 2260

Efficient from top to bottom

- avoid slow work in unhealthy working postures

Long, tall and/or wide hedges can present a real challenge. The work is hard and slow, often involving awkward positions. But not when using a hedge cutter. It is designed for the job, and the perfect choice for thuja, yew and hard beech hedges.

The hedge cutter is stable, manoeuvrable and easy to adjust - it works equally well on the left or the right side of the utility machine. It cuts vertically from ground level up to a height of 320 cm. And of course horizontal trimming is a breeze - even the widest hedge. The hedge cutter also trims at angles up to 45 degrees, taking care of those hard-to-reach corners.

It always leaves a hedge evenly and attractively trimmed and tackles most terrain without difficulty, thanks to excellent and stable four-wheel balance.

Side or top trimming is set up hydraulically and driver visibility is good no matter where or what is being trimmed.

The hedge cutter should be lubricated regularly during use. An oil sprayer is, therefore, fitted to the hedge cutter, so oil is available as and when it is needed.

The hedge cutter is equipped with release springs. These protect the cutter as it will "give" if it presses against hedge branches that are too thick.

The hedge cutter is equipped with a support strut, so it is easy to attach/detach. It is supplied with a protective guard for transportation and storage.

The hedge trimmer is the optimal tool outside of the hedge cutting season, where minor trimming and general "maintenance" of the hedge takes place.

The cutter bar is detached from the main arm and the hedge trimmer attached.

The hedge trimmer is a hydraulic trimmer for trimming lighter hedges with branches up to 25 mm thick. It cuts and shreds the material in one workflow, minimising subsequent cleanup work. The high-speed blade system ensures a clean cut without fraying or tearing the branches.



IMPORTANT INFORMATION

You must put about 100 kg of counterweight or tools on the load when using the hedge trimmer for City Ranger 2260.

Video



EGHOLM

Hedge cutter

- City Ranger 2260



Standard equipment:

- Protective guard** For mounting on the cutter bar during transport and storage.
- Support strut** The hedge cutter is equipped with support strut which are used when dismounting the tool for secure parking.
- Holder** To always have spray oil to hand, a holder for spray oil is mounted on the vertical boom.

Extra equipment (options):

- Hedge trimmer** See datasheet on next page.

Technical specifications

Dimensions

Length	mm	3500
Width	mm	1600
Height with cabin / roll bar (ROPS)	mm	1939 / 2060

Storage dimensions

Length	mm	1000
Width	mm	1600
Height	mm	1450

Weights

Weight (cutter)	kg	25
Weight (arm)	kg	115

Performance

Cutting width	mm	1300
Cutting height, max. *	mm	3200
Horizontal cutting height *	mm	0-2100
Horizontal reach *	mm	0-2500
Branch thickness, max.	mm	25
Operating speed	km/h	0-2
No. of blades	pcs.	36
Oil consumption	l/min.	25

CE certified according to EU directive

* The cutting boom range is stated with mounted cutter bar.





Hedge trimmer

- City Ranger 2260



Standard equipment:

Support legs The hedge trimmer is equipped with support legs which are used when dismounting the tool for secure parking.

Holder To always have spray oil to hand, a holder for spray oil is mounted on the vertical boom.

Extra equipment (options):

Cutter See datasheet on previous page.

Counterweight It is recommended to use a counterweight on the back of the City Ranger 2260 when using the hedge trimmer.

Technical specifications

Dimensions

Length	mm	4000
Width	mm	1400
Height with cabin / roll bar (ROPS)	mm	1939 / 2060

Storage dimensions

Length	mm	1000
Width	mm	500
Height	mm	1600

Weights

Weight (trimmer)	kg	48
Weight (arm)	kg	115

Performance

Trimming width	mm	1300
Trimming height, max. *	mm	2700
Horizontal trimming height *	mm	300-2100
Horizontal reach *	mm	1850
Branch thickness, max.	mm	25
Operating speed	km/h	0-2
No. of blades	pcs.	3
Oil consumption	l/min.	20-28

CE certified according to EU directive

* The cutting boom range is stated with mounted trimmer.



Honest Work,

Egholm A/S develops, produces and markets utility machines that keep roads, parks and outdoor areas clean and inviting all year round. We supply functional quality machines and attachments to people who do an honest day's work keeping our cities clean and attractive. With special attachments developed for the machines, Egholm machines deliver perfect results no matter the task at hand. Built by craftsmen in Denmark, Egholm machines are in operation in cities and parks all over the world.

Honest Machines,

Egholm utility machines are developed by people who are passionate about technology and innovation. We listen to the people driving, using and servicing Egholm machines, because they are the true experts. It is our mission to design, build and market utility machines that deliver perfect results in real life. Egholm machines are honest machines - not just because they deliver comfort, safety and strong end results: They are also a sound investment for years to come and give you outstanding return on your investment.

Honest People,

We want you to think of us as your partner in every single way. And we always insist on reliability, trust and honesty in our partnership with you and with our network of dealers and service partners. We are straightforward and direct in our communication and in our dealings with everyone. Our belief in hard work and unwillingness to compromise helps us deliver the quality for which we are known. And we believe it is reflected by the machines we build for you, as well.

Egholm A/S

Transportvej 27
7620 Lemvig, Denmark
T.: +45 97 81 12 05
www.egholm.eu - info@egholm.dk

Egholm GmbH

Am Hafen 24
38112 Braunschweig, Germany
T.: +49 (0) 531 129 77-0
www.egholm.de - info@egholm.de