


## Basic machine

### - Park Ranger 2150



#### Standard equipment:

- Drive** Hydraulic drive. Pure hydraulic-driven utility machine only requiring minimal maintenance.
- Hydraulics** The oil type is Rando HDZ 68, tank capacity is 15 l. Working pressure of up to 180 bar.
- Lights and mirrors** For machines with cabin EU standard driving lights are placed at the top of the cabin and side mirrors at the side of the cabin.  
  
Machines without cabin are fitted with stop and indicator lights at the back of the machine.
- 12-volt socket** For mobile phone charger.
- Coupling** TÜV approved (acc. ECE R55).

#### Extra equipment (options):

- Radio** Bluetooth radio with USB port and SD slot or DAB+ radio with Bluetooth. Headset included.
- Large radiator cover** Fit your Park Ranger 2150 with the large radiator cover when cutting grass, as the cover protects the engine against overheating.
- Load carrier** A practical little load carrier that provides room to transport hand tools.
- Shovel and broom holder** A little smart option that provides room to bring a shovel and a broom on the machine.
- Anti-corrosion treatment** The anti corrosion treatment of the basic machine is recommended when operating in the winter season.

#### Technical specifications

Dimensions		
Length	mm	2225
Width	mm	1015
Height with / without cabin	mm	1935 / 1210
Weights & other data		
Weight with / without cabin <sup>1)</sup>	kg	670 / 560
Payload with / without cabin	kg	630 / 740
Gross vehicle weight	kg	1300
Allowed axle load, front	kg	740
Allowed axle load, back	kg	740
Max. permitted trailer weight without brakes	kg	750
Max. combined weight without brakes	kg	2050
Max. permitted trailer weight with brakes	kg	1500
Max. combined weight with brakes	kg	2800
Performance		
Turning circle - kerb to kerb	mm	3000
Turning circle - inside	mm	1100
Operating speed, max.	km/h	16
Noise level		
Passing (Outside - 2009/63/EC)	dB(A)	N/A
Operators seat (Inside - 2009/76/EC)	dB(A)	N/A
Engine		
Model	Perkins diesel 403J-11	
EU norm	Stage V	
Engine power	hp/kW	26 / 19
Fuel tank capacity	l	20
Fuel consumption at 2400 rpm (EN 15429-2)	l/h	2,8
Fuel consumption at 3400 rpm (EN 15429-2)	l/h	4,6
CE certified according to EU directive		

<sup>1)</sup> Includes: 75 kg operator and 90% fuel capacity.

