


## Flail mower

### - Park Ranger 2150



#### Standard equipment:

**Clearing height adjustment** The clearing height is adjusted using the two forward wheels (rough and fine adjustment). Rough adjustment using seven adjusting rings in interval 0-110 mm. Fine adjusting carried out by a variable-adjustable lever.

#### Extra equipment (options):

**Verticutter knives** Changing the flails with vertical blades converts the flail mower into a verticutter, which deals with moss and weeds without the need for pesticides. The verticutter removes moss while simultaneously cutting a thin score in the turf, so the grassroots are aired. This strengthens the grass so the turf is much more resilient to weeds.

**Counterweight** It is recommend to use a counterweight on the back of the Park Ranger 2150 when using the flail mower. (2 x 18,5 kg)

**Radiator cover** It is recommend to use a radiator cover for mowing in very dry grass and dusty surroundings, as this stops the radiator from becoming choked with grass and protects the motor.

#### Technical specifications

<b>Dimensions</b>		
Length	mm	2895
Width	mm	1475
Height with / without cabin	mm	1935 / 1210
<b>Storage dimensions</b>		
Length	mm	955
Width	mm	1475
Height	mm	435
<b>Weight</b>		
Weight (flail mower / verticutter)	kg	154 / 151
<b>Performance</b>		
No. of flails	pcs.	76
No. of vertical blades (max.)	pcs.	38
Flail - clearing width	mm	1226
Flail - clearing height	mm	1-110
Rotation of blades	rpm	2800
Verticutter - clearing width	mm	1172
Verticutter - clearing depth	mm	0-15
<b>CE certified according to EU directive</b>		

