

Load carrier with tip - Park Ranger 2155



920 mm



2470 mm



1350 mm
1987 mm

Standard equipment:

- Hydraulic tipping** The hydraulic tipping action makes it fast and easy to empty the load carrier with tip.
- Removable sides** The volume can be adjusted with the removable sides.
- Lockable back flap** The back flap can be locked in the horizontal position to allow for the transportation of planks, garden tools etc.
- Stand** The supplied stand allows for simple and quick fitting and removal of the load carrier with tip. One person can therefore easily attach / detach the load carrier with tip alone.

Technical specifications

Dimensions

Length	mm	2470
Width	mm	930
Height with / without cabin	mm	1987 / 1350

Storage dimensions

Length with stand	mm	1400
Width with stand	mm	930
Height with stand	mm	1360

Weights

Weight with / without cabin ¹⁾	kg	834 / 692
Payload with / without cabin	kg	466 / 608
Weight (load carrier with tip)	kg	94

Performance

Platform, length	mm	1040
Platform, width	mm	860
Platform, height	mm	300/600
Volume	m ³	0,4
Load carrying capacity, max.	kg	300
Loading height	mm	700-1040

CE certified according to EU directive

¹⁾ Includes: load carrier, 75 kg operator and 90% fuel capacity.

