

Snow V-plough - Park Ranger 2155



1400 mm



2590-3010 mm



1350 mm
1987 mm

Standard equipment:

- Hydraulic angle adjustment** Each side/blade can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blades when needed.
- Vibration damping** A-frame featuring integrated vibration damping, which increases comfort and reduces noise.
- Vulkollan scraper edge** The vulcanised rubber scraping edge is good for surfaces that require extra care. The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either vulcanised rubber scraper or steel scraper.
- Steel scraper edge** The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow V-plough can be mounted with either steel scraper or vulcanised rubber scraper.
- Safety tilt function** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function of lower part of the V-plough reduces the risk of damages both to the plough and surroundings.
- Floating skids** The 2 skids are height adjustable and ensures that the plough follows ground variations.

Extra equipment (options):

- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	2590-3010
Width (straight)	mm	1400
Height with / without cabin	mm	1987 / 1350

Storage dimensions

Length	mm	500
Width	mm	1200
Height	mm	600

Weight

Weight (snow V-plough)	kg	108
------------------------	----	-----

Performance

Clearing width - straight	mm	1400
Clearing width - inclined	mm	1200-1400
Clearing width - 30°, Y- & V-form	mm	1200
Ground clearance below scraper	mm	140
Ground clearance under support strut	mm	125
Operating speed	km/h	1-16
Handling snow depth up to	mm	500
Turning angle		30°
Theoretical performance	m ² /h	22400

CE certified according to EU directive

