EGHOLM

- Park Ranger 2155





Standard equipment:

Steel chassis	The tipper trailer features a strongly built steel chassis with fixed headboard and sides.	
Hydraulic tip function	The unloading of the 0,44 $\rm m^3$ trailer is easily done via the joystick from the comfort of the driver seat.	
Support wheel	The support wheel allows for easy attaching, detaching and storage.	
Extra equipment (ontions):		

Extra equipment (options):

Side extensions	The optional side extensions increase the volume of the trailer. The side extensions are 40 cm in the height.
Lighting	The galvanized beam with rear lights makes the trailer visible in traffic.

Technical specifications

Dimensions		
Length	mm	4370
Width	mm	1025
Height with / without cabin	mm	1987 / 1350
Storage dimensions		
Length	mm	2100
Width	mm	1025
Height	mm	850
Weights		
Weight with / without cabin 1)	kg	878 / 736
Payload with / without cabin	kg	422 / 534
Weight (tipper trailer)	kg	138
Performance		
Platform, length	mm	1500
Platform, width	mm	950
Platform, height	mm	310
Platform, height with optional side extensions	mm	350
Volume	m³	0,44
Volume with side extensions	m³	1,02
Load carrying capacity, max.	kg	440
Loading height	mm	850
CE certified according to EU directive		

¹⁾ Includes: tipper trailer, 75 kg operator and 90% fuel capacity.



