



Rotary/mulch mower 1200

- Park Ranger 2155e

Standard equipment:

Tilting for cleaning	The mower can tilt up and rest on two support wheels making cleaning easy.
Stepless height adjustment	Cutting height can be infinitely adjusted via handle on the mower.
Piano wheels	Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in their wheel forks for durability.
Lawn protection screens	The lawn protection screens protect both the blades and the lawn. The screens prevent larger sharp or hard objects from hitting the knives, thereby reducing wear of the knives. The screens also protect the lawn, as you avoid them running down into the lawn if the mower is lowered too much.

Extra equipment (options):

Mulch mower kit	The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.
------------------------	--



Technical specifications

Dimensions		
Length	mm	2850
Width	mm	1280
Height with / without cabin	mm	1987 / 1350
Storage dimensions		
Length	mm	980
Width	mm	1280
Height	mm	480
Weights		
Weight with / without cabin ¹⁾	kg	931 / 791
Payload with / without cabin ¹⁾	kg	569 / 709
Weight (rotary mower)	kg	96
Performance		
Ground clearance below mower	mm	110
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1210
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m ² /h	12100
Theoretical mowing area - mulch	m ² /h	12100
Max. recommended operating speed		
Rotary mower *	km/h	10
Mulch mower (shorter grass) *	km/h	10
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	104
CE certified according to EU directive		

* Depends on grass and height.

¹⁾ Includes: rotary mower 1200 and 75 kg operator.

