

Snow V-plough - Park Ranger 2155e



1400 mm



2590-3010 mm

1350 mm
1987 mm

Standard equipment:

- Hydraulic angle adjustment** Each side/blade can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blades when needed.
- Vibration damping** A-frame featuring integrated vibration damping, which increases comfort and reduces noise.
- Vulkollan scraper edge** 125 mm high, 25 mm thick and 700 mm wide. The vulcanised rubber scraping edge is good for surfaces that require extra care. The snow V-plough can be mounted with either vulcanised rubber scraper or steel scraper.
- Steel scraper edge** The snow V-plough can be mounted with either steel scraper or vulcanised rubber scraper.
- Safety tilt function** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function of lower part of the V-plough reduces the risk of damages both to the plough and surroundings.
- Floating skids** The 2 skids are height adjustable and ensures that the plough follows ground variations.

Extra equipment (options):

- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	2590-3010
Width (straight)	mm	1400
Height with / without cabin	mm	1987 / 1350

Storage dimensions

Length	mm	500
Width	mm	1200
Height	mm	600

Weights

Weight with / without cabin ¹⁾	kg	943 / 803
Payload with / without cabin ¹⁾	kg	557 / 697
Weight (snow V-plough)	kg	108

Performance

Clearing width - straight	mm	1400
Clearing width - inclined	mm	1200-1400
Clearing width - 30°, Y- & V-form	mm	1200
Ground clearance below scraper	mm	140
Ground clearance under support strut	mm	125
Max. recommended operating speed	km/h	16
Handling snow depth up to	mm	500
Turning angle		30°
Theoretical performance	m ² /h	22400

CE certified according to EU directive

¹⁾ Includes: snow V-plough and 75 kg operator.

