



# Snow plough

## - Park Ranger 2155e

### Standard equipment:

**Safety tilt system** When operating in deep snow there is a risk of hitting obstacles. The safety tilt function reduces the risk of damages both to the plough and surroundings.

**Rubber scraper edge** 100 mm high, 25 mm thick and 1300 mm wide rubber scraper. The scraper edge can be used on two sides giving double usage and extended lifetime. The rubber scraping edge is ideal for use with melting snow and also scrapes the surface thoroughly without damaging it.

**Floating skids** The 2 skids are height adjustable and ensures that the blade follows ground variations.

### Extra equipment (options):

**Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.



1300 mm



2700 mm

1350 mm  
1987 mm

### Technical specifications

#### Dimensions

Length	mm	2700
Width	mm	1300
Height with / without cabin	mm	1987 / 1350

#### Storage dimensions

Length	mm	550
Width	mm	1300
Height	mm	545

#### Weights

Weight with / without cabin <sup>1)</sup>	kg	899 / 759
Payload with / without cabin <sup>1)</sup>	kg	601 / 741
Weight (snow plough)	kg	64

#### Performance

Clearing width - straight	mm	1300
Clearing width - inclined	mm	1130
Ground clearance below scraper	mm	400
Ground clearance under support strut	mm	350
Max. recommended operating speed	km/h	16
Handling snow depth up to	mm	350
Turning angle		30°
Theoretical performance	m <sup>2</sup> /h	20800

#### CE certified according to EU directive

<sup>1)</sup> Includes: snow plough and 75 kg operator.

