



Snow sweeper

- Park Ranger 2155e



1220 mm



3090 mm



Standard equipment:

Trapeze mounting The trapeze-mounting ensures the snow sweeper remains clear of the wheels of the utility machine at all times, whatever the angle. The snow sweeper automatically turns with the utility machine - always sweeping in front of the wheels of the utility machine.

Reverse rotation function Reversing the brush rotation ensures that the operator can sweep material when reversing out of an alley or parking spot, which ensures an excellent result.

Adjustable speed The rotation speed can easily be adjusted from the cabin to match the need for sweeping.

Support stand A support stand with a wheel is built into the snow sweeper for easy storage.

Extra equipment (options):

Extended brush guard Attaching a brush guard extends the snow sweeper cover, which minimises the snow whirling up on the front wind-screen. Furthermore, the guard makes it easier to control the direction of swept sand and gravel during summer operation. This can be retrofitted on existing snow sweepers as well.

Anti-corrosion treatment The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	3090
Width	mm	1220
Height with / without cabin	mm	1987 / 1350

Storage dimensions

Length	mm	900
Width	mm	1220
Height	mm	650

Weights

Weight with / without cabin ¹⁾	kg	939 / 799
Payload with / without cabin ¹⁾	kg	561 / 701
Weight (snow sweeper)	kg	104

Performance

Clearing width - straight	mm	1220
Clearing width - angled 25°	mm	1140
Ground clearance below brush	mm	420
Brush diameter Ø	mm	550
Max. recommended operating speed	km/h	10
Theoretical sweeping capacity	m ² /h	12200
Handling snow depth up to	mm	150
Brush speed	rpm	255
Turning angle		25°

CE certified according to EU directive

¹⁾ Includes: snow sweeper and 75 kg operator.

