



Tipping shovel

- Park Ranger 2155e

Standard equipment:

Lifting capacity: 100 kg The tipping shovel makes light work of transporting gravel, sand or mould and saves the operator many lifts during the working day. 100 kg is easily transported from one place to another - even on the narrowest paths.

Hydraulic tipping function

The hydraulic tipping function ensures an easy handling and is perfect when unloading over obstacles like for example small hedges. The transported material is spread evenly by unloading. For a perfect result level the layer with the edge of the shovel.

Robust steel construction

The shovel features a robust steel construction, which enables it to manage a variety of different applications besides transporting material, for example to scrape off unwanted grass growth from flagged areas.



1045 mm



2840 mm

1987 mm
1350 mm

Technical specifications

Dimensions

Length	mm	2840
Width	mm	1045
Height with / without cabin	mm	1987 / 1350

Storage dimensions

Length	mm	670
Width	mm	1045
Height	mm	405

Weights

Weight with / without cabin ¹⁾	kg	875 / 735
Payload with / without cabin ¹⁾	kg	625 / 765
Weight (tipping shovel)	kg	40

Performance

Volume	l	66
Lifting capacity	kg	100
Ground clearance under shovel	mm	480

CE certified according to EU directive

¹⁾ Includes: tipping shovel and 75 kg operator.

