New

EGHOLM APPROVED

RALA TECH & STEEL

EGHOLM

NoWeed weed control system

- City Ranger 2260

1068 mm

4020 mm

1989 mm
2060 mm

Standard equipment:

Water heating
Digitally controlled boiler ensures precise temperature control and constant heat for effective and uniform weed control. Water temperature is maintained at 98 degrees.
Insulated system reduces heat loss during operation, improving energy efficiency and contributing to more economical operation.

Operation and control
Quiet operation makes the system ideal for use in urban areas and other noise-sensitive areas.
Intuitive control panel makes it easy to control all functions and ensures that the machine is quickly ready for use in daily work.

Lance
Weed lance with adjustable side handle.
Lance head Ø150 mm.

Hose system
20 meter stainless steel hose reel.

Frame
The machine is built for demanding professional use with a focus on durability and reliability. The choice of materials and construction ensure a long service life even under intensive working conditions.

Stand
The included stand allows for quick and easy assembly and disassembly of the system - without the need for tools. The stand is also used for storing the system when not in use.

Battery charger
The integrated battery charger is plugged in every evening and ensures a fully charged system for a full day's work. Battery charger is a 230 volt charger. Batteries are charged from 10 % to 90 % in a maximum of 7 hours.

Filters
Replaceable water filter and anti-lime scale system.

Service kit
Descaler and anti-freeze kit.

Extra equipment (options):

Front boom with swivel nozzle head
Front boom with nozzle head is hydraulically operated from the cabin. The water supply is started and stopped as needed. Nozzle head: 200 x 300 mm.

Technical specifications

Dimensions		
Length	mm	2500
Length with front boom	mm	4020
Width	mm	1068
Height with cabin / roll bar (ROPS)	mm	1989 / 2060
Storage dimensions		
Length with stand	mm	1250
Width with stand	mm	920
Height with stand	mm	2500
Weights		
Weight with cabin / roll bar (ROPS) [1)]	kg	1245 / 1215
Weight with cabin / roll bar (ROPS) - with front boom [1)]	kg	1300 / 1270
Payload with cabin / roll bar (ROPS) [1)]	kg	365 / 395
Payload with cabin / roll bar (ROPS) - with front boom [1)]	kg	310 / 340
Weight (NoWeed weed control system)	kg	305
Weight (NoWeed front boom)	kg	55
Performance		
Fresh water tank capacity	l	300
Fuel tank capacity (diesel)	l	22
Battery operating time, min.	hours	6
Battery, capacity	Ah	180
Pump pressure	bar	7
Water flow, min.	l/min.	4,5
Water flow, max.	l/min.	7
Max. recommended operating speed with front boom	km/h	1
CE certified according to EU directive		

[1)] Includes: NoWeed weed control system, 75 kg operator and 90% fuel capacity.

Important information !!!
The attachment in question is a separate, CE marked product manufactured by a third party supplier. The attachment is supplied and marketed as a standalone product and is not an integrated part of the Egholm machine. The Egholm machine functions as a utility machine and, in working mode, can provide hydraulic and/or electrical power as well as operation via joysticks or predefined operating programmes. These functions relate exclusively to the operation of the utility machine and do not alter the attachment's design, safety or CE status.
The attachment's EU conformity, including the EU Declaration of Conformity and technical documentation, is the responsibility of the manufacturer.

Specifications and details are subject to change without prior notice. Illustrations can be shown with extra equipment.