

New

EGHOLM

Rotary mower 1500 for grass collection

- City Ranger 3070

(in combination with grass collector)

Standard equipment:

Hydraulic tipping function	Using the control handle, the cutter can be tipped into vertical position for easy cleaning and maintenance of the cutter.
Hydraulic height adjustment	The cutting height is adjustable using the hydraulic system of the machine.
Mower blades	Self-developed mower blades for optimal cutting results.
Piano wheels	Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in their wheel forks for durability.
Reverse function	The machine periodically reverses the air flow through the radiator to blow grass, etc., away from the radiator and intake grilles. This protects the engine and components.
Lawn protection screens	The lawn protection screens protect both the blades and the lawn. The screens prevent larger sharp or hard objects from hitting the knives, thereby reducing wear of the knives. The screens also protect the lawn, as you avoid them running down into the lawn if the mower is lowered too much.
Floating function	The floating function provides optimal terrain adaptation of the mower. For example, in very wet conditions, the floating function can be used to reduce the weight of the mower against the terrain.

Extra equipment (options):

Tyres 235/60 R 16 (M+S)	These tyres can be used universally (summer and winter) and generate less ground pressure than the narrower 195/75 R 16 tyres.
Tyres 27 x 10.50-15 BKT	The BKT lawn tyres are mainly intended for use on sensitive green areas. Due to the large contact surface, they generate very little ground pressure.

To be used in combination with grass collector - see separate datasheet.



2100 mm
2000 mm
1582 mm
4570 mm

Technical specifications

Dimensions

Length (with mower 1500)	mm	4570
Width (with mower 1500)	mm	1582
Height / with beacon	mm	2000 / 2100

Storage dimensions

Length	mm	990
Width	mm	1582
Height	mm	1000

Weights

Weight (rotary mower for grass collection)	kg	155
--	----	-----

Performance

Ground clearance below mower	mm	140-190
No. of mower blades	pcs.	3
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1500
Adjustable cutting height	mm	30-80
Theoretical mowing area - rotary	m ² /h	9000

Max. recommended operating speed

Collection mower *	km/h	6
--------------------	------	---

Noise emissions

Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	107
--	-------	-----

CE certified according to EU directive

* Depends on grass and height.

