

Video



Triplex rotary mower 2500

- City Ranger 3070

EGHOLM



Standard equipment:

Hydraulic controlled cutting wings

From the joystick in the cabin, the wings of the cutter can be adjusted according to your needs: both wings up, down or individual positions. Thereby, the cutting width can be adjusted to the task when you have a narrower space or when a larger lawn needs to be mowed. The possibility of making the width smaller with wings in an upright position is also an advantage during transport to and from the task.

Hydraulic tipping function

From the joystick in the cabin, the cutter can be tipped for easy cleaning and maintenance of the cutter or, if wished, a change of blades.

Manual height adjustment

The cutting height can be adjusted by moving the height rings on each of the wheels on the mower.

Specially developed blades

The cutter is as standard equipped with specially developed 4-in-1 blades which ensure a nice cutting result.

Piano wheels

Piano wheels (6 pcs.) move the cutter in line with the manoeuvring.

Reverse function

The machine provides the absolute best conditions for air supply and cooling by means of temporary air reversal through the cooling unit, which blows away any grass inside the intake grid.

Floating function

After lifting the mower it quickly returns to the floating position.

Extra equipment (options):

"Low lift" blades

The blades can be replaced with "Low lift" knives, which due to their design, give smaller bio cuts. Suitable for cutting short grass and used in dry conditions.

Mulch mower kit

The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.

Chain guard kit

Installing a chain guard prevents stones and other objects from being thrown away to the danger of passers-by.

Lawn protection screens kit

The lawn protection screens protect both the blades and the lawn. The screens prevent larger sharp or hard objects from hitting the knives, thereby reducing wear of the knives. The screens also protect the lawn, as you avoid them running down into the lawn if the mower is lowered too much. A kit consists of 5 pcs. screens.

Tyres 235/60 R 16 (M+S)

These tyres can be used universally (summer and winter) and generate less ground pressure than the narrower 195/75 R 16 tyres.

Tyres 27 x 10.50-15 BKT

The BKT lawn tyres are mainly intended for use on sensitive green areas. Due to the large contact surface, they generate very little ground pressure.



Technical specifications

Dimensions

Length	mm	5047
Width	mm	1880-2535
Height / with beacon	mm	2000 / 2210

Storage dimensions

Length	mm	1550
Width	mm	1880-2535
Height	mm	500

Weight

Weight (rotary mower)	kg	365
-----------------------	----	-----

Performance

Ground clearance below mower	mm	250
No. of mower blades	pcs.	5
Cutting width, both wings down	mm	2480
Cutting width, one wing down	mm	2007
Cutting width, both wings up	mm	1533
Adjustable cutting height	mm	30-80
Theoretical mowing area	m ² /h	24800

Max. recommended operating speed

Rotary mower *	km/h	10
----------------	------	----

Noise emissions

Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	107
--	-------	-----

CE certified according to EU directive

* Depends on grass and height.